

Rubiomonocoat EXTERIOR REFRESH

DESCRIPTION:

Rubio Monocoat Exterior Refresh is a revitalising treatment oil that was developed for the maintenance of exterior wood that has been treated with Decking Oil 2C. Existing hairline cracks can be reprotected from UV damage and water in order to ensure long-lasting protection.

SPECIAL PROPERTIES:

Since wood is a living material and therefore subject to shrinkage and expansion, microscopic hairline cracks will occur after some time. This is especially the case for decking that has been standing under pools of water, snow, or suffered the effects of UV rays and wear through walking on it. Maintenance with **Rubio Monocoat Exterior Refresh** will reprotect these hairline cracks.

DIRECTIONS FOR USE:

1. In principle, it is sufficient to just use water to pre-clean the surface. If there is some greying, add some **Rubio Monocoat Exterior Wood Cleaner**.
2. Apply the product with a rag, roller with fleece cover, sponge or nebulizer and rub it in.
3. Allow the **Rubio Monocoat Exterior Refresh** to soak in for 10 to 15 mins. Wipe off any excess product.
4. Drying time: 6 to 8 hours. Can be walked on after 8 to 12 hours.

Clean the used materials with **Rubio Monocoat Cleaner**.

FREQUENCY:

Decking treated with RMC Decking Oil 2C: 1 to 2 times per year depending on wear.

USAGE:

30 to 50 m² per liter.

These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.

TECHNICAL SPECIFICATIONS:

Oil

Unit weight: +/- 0,90

Colour: opaque

Odour: specific

PACKAGING:

400 ml spray, 1 liter – 5 liter can.

STORAGE:

The product can be stored for up to 12 months in a dry place and in the original packaging.

CAUTION:

The product may NOT be diluted!
Cloths, saturated with oil, may spontaneously combust.
After usage, they need to be soaked in water before disposal.

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.

PROVIDED BY:



Consult the safety sheet before use.

Date TDS: 30/08/10.

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

